

## TA-141 Single Head Miter Saw (Ø:350 mm-13.77 in.)

SAWS » TA-141




- For Aluminum profiles cutting.
- Pneumatic saw blade feed from below with 350 mm (13.77 in.) saw blade diameter.
- The saw blade feed speed can be adjusted.
- Wide cutting angle range from 22.5° to 157.5° with special location points at 45°, 90° and 135°.
- Vertical pneumatic clamps ensure optimum profile clamping.
- Filter-Regulator-Lubricator for incoming air supply.
- Pulse spray mist blade lubricant system.

## **OPTIONAL**

- Left and right roller stock conveyor system (TK 060)
- 3m (118.11 in.) Right hand roller stock conveyor & measuring stop (TK 061)
- 3m (118.11 in.) Left hand roller stock conveyor & measuring stop (TK 062)
- Automatic measuring and positioning system (MS 300)
- Hydro-Pneumatic System for Aluminum profiles. (AH 041)





## **Technical Features:**

<ul> <li>Power supply: 400V, 3 ~, 50/60 Hz</li> </ul>	<ul> <li>Machine height: 1300 mm (51.18 in.)</li> </ul>
Total Power Output: 2.2 kW (2.94 hp)	Machine length: 800 mm (31.49 in.)
• Spindle speed: 2800 rpm (50 Hz), 3360 rpm (60 Hz)	Machine width: 700 mm (27.55 in.)
Working air pressure: 6-8 bar (90-120 psi)	Machine weight: 195 kg (430 lbs.)
Air consumption: 95 I/min. (3.35 cfm)	

<sup>\*</sup> Consult factory for lengths and specifications not mentioned above.